



ISSUE	AMENDMENT	DATE
△ <sup>3</sup>	CANCEL THE POST	07.08.02
△ <sup>1</sup>	UPDATE THE PET	07.08.03

**PIN ASSIGNMENT:**

1	2	3	4	5	6	7	8	9	10	
NC	NC	NC	IM3	NC	RESET	VSYNC	HSYNC	DOTCLK	ENABLE	
11	---	28	29	30	31	32	33	34	35	36
DB17	---	DB0	RD	WR	DC	CS	VSS	VCC	LED-	LED+

- NOTES:**
- 1. ◊ : SPECIAL CHARACTERISTIC
  - 2. + : SAFETY CHARACTERISTIC
  - 3. ▽ : CRITICAL DIMENSION
  - 4. ( ) : REFERENCE DIMENSION

DISPLAY TYPE	TFT, TRANSMISSIVE 262K COLOR	
DISPLAY RESOLUTION	240XRGBX320	
VIEWING ANGLE	12 O' CLOCK	
MUX RATIO	TBD	
LCD CONTROLLER /DRIVER	TBD	
LOGIC VOLTAGE	~2.8V(TYP)	
OPERATING TEMPERATURE	-20°C to +70°C	
STORAGE TEMPERATURE	-30°C to +80°C	
BACKLIGHT	TYPE	LED05
	COLOR	White
	WAVELENGTH	-
	DRIVING VOLTAGE	-9.6V, @15mA
	LUMINANCE(E6/m2)	Min. --
	ION-THE BACKLIGHT SURFACE)	Typ: 3200cd/m² Max. --

MULTI-INNO TECHNOLOGY CO.,LTD.

TITLE: SPECIFICATION OF MODULE		
PROJECT NO: MI0240JT		
CUSTOMER REF:		
TOLERANCE UNLESS OTHERWISE SPECIFIED:		X.X ±0.3 X.XX ±0.1
DIMENSIONS IN MM		ANGULAR: ± 1°
MATERIAL: N/A		FINISH: N/A
SCALE: DO NOT IN SCALE		OVERALL THK: N/A
THIRD ANGLE PROJECTION		
	NAME	SIGN DATE
DRAWN:	ANNA HE	07.08.03
CHECKED:	TOM SUN	
APPROVED:	HENRY HE	
ITEM NO.: MI0240JT		
DESCRIPTION:		
FILE NO:		VER2
SHEET	1 OF 1	