




## ADSL Transformers for Fujitsu Chipsets

### Features


- complies with ANSI and ETSI requirements
- matched to Fujitsu's Keywave MB86670 chipsets
- very low THD
- 1500V minimum isolation
- all materials approved to UL94V-0
- excellent quality at competitive price due to high volume production
- manufactured in ISO-9001 approved Talema facility



### Electrical Specifications @ 25°C • Operating Temperature -40° to +85°C

Part Number	Package	IC Driver	Turns Ratio ±2% Line : IC	L <sub>P</sub> (mH) ±6%	L <sub>L</sub> (µH) Max	C <sub>ww</sub> (pF) Max	DCR (Ohms) Max Line / IC	THD (Linearity) Typical	Longitudinal Balance Min	Insertion Loss Max	Frequency Response Max	Isolation Voltage (Vrms)
AEP800-T	TH	MB86670 CO	2 : 1	2.0	12	60	2.50 / 1.30	-80dB 100kHz	-40dB 30kHz-1.1MHz	0.5dB 100kHz	0.5dB 30kHz-1.1MHz	1500
AEP800-S	SMD											


#### Package "S"




Dimensions: Inches(Millimeters)  
Tolerance: ±0.010 (0.25)

Weight: 6.8 grams

#### Package "T"



#### Schematic



## Sales & Marketing, Design and Manufacturing Facilities

<http://www.talema-nuvotem.com>

### Eastern Europe & Czech Republic

NT MAGNETICS s.r.o.  
Chebská 27  
322 00 Plzeň  
Tel: Int. + 420 37 - 744 9303  
Fax: Int. + 420 37 - 744 3697  
Email: talema@talema.cz

### Germany

TALEMA ELEKTRONIK GMBH  
Sembdnerstr. 5, Postfach 2523  
82110 Germering  
Tel: Int. + 49 89 - 841 00 - 0  
Fax: Int. + 49 89 - 841 00 25  
Email: info@talema.de

### Ireland

NUVOTEM TEO.  
Crollý  
Co. Donegal  
Tel: Int. + 353 74 - 954 8666  
Fax: Int. + 353 74 - 954 8139  
Email: info@nuvotem.com

### India

TALEMA ELECTRONIC PVT. LTD.  
Opposite the SIDCO Industrial Estate  
Gins Towers  
4/5S.H/1, Omalur Main Road  
Salem - 636 004, Tamil Nadu  
Tel: Int. + 91 427 - 244 1325  
Fax: Int. + 91 427 - 243 0034  
E-mail: talema@talemaindia.com