

## Data sheet

Commercial Art.No.: 80.020.0004.0

Solid state relay WRS-SSAC1-250V6A

WRS-solid-state-relays, 1-phase, solid state relay not plugable, with LED, open module housing WEB 1002, dimensions: 12,5 x 80 mm (W xH), control voltage: 24 V DC, output 250V AC / 6A (Remark: the negative pole can be linked At the controll side with A jumper to the next module , if needed it has to be ordered seperately).



Commercial Art.No.	80.020.0004.0
EAN	4015573378438
Order Unit	5

Certificates / Approvals



## Technical data

### General

Modular version	No
-----------------	----

### Technical data

Connection type	screw connection
Type of excitation	DC
Min. connection voltage	3 V
Max. connection voltage	60 V
Rated operating current AC-1	6 A
Rated operating current DC	5 A
Min. control voltage	24 V

### Dimensions

Depth	59 mm
Width	12.5 mm
Height	80 mm

### Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055

ETIM 4.0	EC002055
ETIM 3.0	EC002055

**Product compliance**

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1