

Data sheet

Commercial Art.No.: 70.354.1636.3

Hood EX GOT GC16 M32 09IA Z3

Hood revos Ex made of zinc, for double locking lever or. screw cap with trumpet gland M32 on the top (IP54), low version, 16-poles explosion-tested version



Commercial Art.No.	70.354.1636.3
EAN	4015573773714
Order Unit	1

Certificates / Approvals



Technical data

General

Explosion-tested version	yes
Housing material	Die-cast zinc
Color	Blue
Degree of protection (IP)	IP54
Operating temperature range min.	-20 °C
Operating temperature range max.	60 °C

Model

Construction	16
Model of the housing	male
Locking mechanism	Double locking levers
Cable entry	Above
Type of cable	Gland nut
With cable screw gland	yes
Thread size M	32
Thread size PG	
EMC-version	No
Length	94 mm
Width	56 mm
Height	53 mm

Classification

ECLASS 11	
-----------	--

ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437
ETIM 5.0	EC000437

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(a); III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1