

Data sheet

Commercial Art.No.: 81.000.6322.0

Switched-mode power supply WIPOS PB1 12-2

wipos switched-mode power supply, nominal voltage: 12 V DC / 2 A, (setting range 12-14 V DC) sustained short-circuit protection, input voltage range: 90-264 V AC / 120-375 V DC, single phase, DIN rail mounted device 2 mod



| | |
|--------------------|---------------|
| Commercial Art.No. | 81.000.6322.0 |
| EAN | 4049088106163 |
| Order Unit | 1 |

Technical data

General

| | |
|--------------------------------------|---------------------------|
| Connection type | screw connection |
| Number of phases | Single phase power supply |
| Modular version | yes |
| Mounting type, other | No |
| Mounting type, wall mounting | No |
| Rail mounting possible | yes |
| Housing material | Plastic |
| Operating temperature min. | -40 °C |
| Operating temperature max. | 71 °C |
| relative humidity min. | 20 % |
| relative humidity max. | 95 % |
| Storage temperature / transport min. | -40 °C |
| Storage temperature / transport max. | 85 °C |
| Degree of protection (IP) | IP20 |
| Pollution degree | 2 |
| Parallel-service possible | No |

Technical data

| | |
|---------------------------------|-------------------------------------|
| Function display | "DC OK" LED grün (U(o) 9...10,8V) |
| function display "DC Low" | "DC LOW" LED rot (U(o) < 9...10,8V) |
| Short-circuit protective device | Current limiting (hiccup mode) |
| temperature coefficient | ±0,03%/K |
| ripple and noise | < 0.05 V |
| hold time 115V AC | > 20 ms |
| hold time 230V AC | > 100 ms |
| isolating voltage Output DC | 4242 V |

| | |
|----------------------------------|--|
| cohesive resistance (In-/Output) | 100 MOhm |
| Derating | 61°C...71°C: 2,5 %/K |
| cooling | free convection |
| MTBF | 798.000h |
| Connector cross section (input) | min. 0,5mm ² (AWG24) max. 2,5mm ² (AWG12) |
| Connector cross section (output) | min. 0,5mm ² (AWG24) max. 2,5mm ² (AWG12) |
| Wire strip length | 7 mm |
| Permissible torque max. | 0.6 Nm |
| Control "Adj" | trimming potentiometer for fine-tuning of U(out) |
| CE-Norm | EN61000-6-3, EN 55022 Class B, EN61000-3-2, EN61000-3-3, EN61000-6-2, EN55024, EN61000-4-2, Level 4, EN61000-4-3 Level 3, EN61000-4-4 Level 4, EN61000-4-5 L-N Level 3, L/N-FG Level 4, EN61000-4-6 Level 3, EN61000-4-8 Level 4, EN61000-4-11, ENV 50204 Level 2, EN61204-3 |
| Approval cULus | UL 508 Listed, UL60950-1 Recognized |
| Number of + | 2 |
| Number of - | 2 |
| Further terminals | L, N |

Output

| | |
|---------------------------|------|
| Type of output voltage | DC |
| Power output | 24 W |
| Output voltage stabilized | yes |
| Output voltage | 12 V |
| Output current | 2 A |

Input

| | |
|---------------------------------|---------------------------------------|
| Type of voltage (input voltage) | |
| Primary voltage range | 90 V |
| Min. input voltage | 90 V |
| Max. input voltage | 264 V |
| Rated frequency min. | 47 Hz |
| Rated frequency max. | 63 Hz |
| Max. starting current | 40 A |
| Input fuse | T2A / 250V (intern) |
| input protection | Varistor (voltage-sensitive resistor) |

Dimensions



| | |
|------------------------------|---------|
| Depth | 56.5 mm |
| Width | 35 mm |
| Height | 91 mm |
| Mounting Distance horizontal | 25 mm |
| Mounting Distance vertical | 25 mm |
| Weight | 130 g |

Classification

| | |
|------------|----------|
| ECLASS 11 | |
| ECLASS 8.1 | 27049002 |
| ETIM 7.0 | EC002540 |
| ETIM 6.0 | EC002540 |
| ETIM 5.0 | EC002540 |

Product compliance

| | |
|------------------------------|-----------|
| ROHS conformity status | Compliant |
| REACH-SVHC conformity status | Compliant |



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung
 seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet.
 The reproduction, distribution and utilization of this document as well as the
 communication of its contents to others without express authorization is prohibited.

Qu - PEE 12/92

| Teile-Nr. / Part-No. | Typ / Type |
|----------------------|----------------|
| 81.000.6310.0 | wipos PB1 24-1 |
| 81.000.6322.0 | wipos PB1 12-2 |
| 81.000.6331.0 | wipos PB1 5-3 |

Weitere Angaben siehe KATALOG oder eKatalog.
 Additional data see CATALOG or eCatalog.

www.wieland-electric.com
eshop.wieland-electric.com

ja/yes Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten.
 Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!

| | | | | | | | | |
|--|-----------------------------|---|--|---|------------------------------|---------|------------------|--|
| Freitoleranz nach General tolerance | | CAD-Zeichnung, keine manuellen Änderungen CAD-Drawing, no manual modifications allowed | | | 1. Verwendung: First Use: | | Blatt: Sheet: | |
| | | Werkstoff/ Material | | 2016 | Tag/ Date | Name | | |
| | | Maßstab/Scale | | gezeichnet drawn | 29.02. | Koetznr | | |
| | | | | geprüft checked | | | | |
| | | | | Normgepr. Stand. check | | | | |
| | | Datei/ File: 031501__01K.DCD | | Ersatz für/ Replacement for: | | | | |
| | | www.wieland-electric.com | | Type | Benennung/ Title | | | |
| | | | | Teilespezifikation / Component specification | | | | |
| Index | Datum/ Blatt Date/ Sheet | Schaltnetzteil / Switching Power Supply | | | | | | |
| Änderung/ Revision | | | | | | | | |

A
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
M1
M2
M3
L
G
i
11.1
12.1
1.1