

## Data sheet

Commercial Art.No.: 70.330.2436.0

Bottom EX GUT GB24 M25 09IA Z0

Bottom-base revos Ex made of zinc, with single locking lever and cable gland M25 on the left side (IP54), low version, 24-polig, explosion-tested version



Commercial Art.No.	70.330.2436.0
EAN	4015573739925
Order Unit	1

Certificates / Approvals



## Technical data

### General

Housing material	Die-cast zinc
Color	Blue
Surface	With powder coating
Degree of protection (IP)	IP54
Operating temperature range min.	-20 °C
Operating temperature range max.	60 °C

### Model

Construction	24
Model of the housing	female
Locking mechanism	Double locking levers
Cable entry	Sideways
Type of cable	Gland nut
With cable screw gland	yes
Thread size M	25
Thread size PG	
EMC-version	No
Length	144 mm
Width	57 mm
Height	55 mm

### Classification

ECLASS 11	
ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437

**Product compliance**

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1