



| | | 尺寸公差(mm) | | | | |
|------------------------------------|-------------------|----------|-------|-------|-------|----------|
| | | 0 | >30 | >60 | >100 | 0.05/1.0 |
| | | ~ | ~ | ~ | ~ | ±T |
| Rated current | 12A | ±0.20 | ±0.30 | ±0.50 | ±0.70 | ±1.00 |
| Rated voltage | 300V | | | | | |
| Coil/Contact dielectric voltage | 4000V/S | | | | | |
| Dielectric voltage between contact | 2500V/S | | | | | |
| Screw torque | 1.0Nm | | | | | |
| External connection wire | 20-14/0.5-2.5W | | | | | |
| Ambient temperature | G/mm ² | | | | | |
| Key controlled symbol | -45~+85℃ | | | | | * |
| Conform to RoHS | | | | | | |

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

| REV | ECN | DESCRIPTION | DRAFT | DATE | SIZE: A4 | TYPE: PRODUCT DRAWING | SCALE: 1:1 | REV | TO-1 |
|-----|-----|-------------|-------|------|----------|-----------------------|------------|-----|------|
| | | | | | | | | | |

| NO. | DESCRIPTION | MATERIAL NO. | QTY | MATERIAL | NOTES |
|-----|---------------------|--------------|-----|----------|-------|
| 2 | B-35A-00A(H) | 30070000089 | 1 | | |
| 1 | DPKF14A-F3-00A(H)-N | 30019000033 | 1 | | |

| | | | |
|-----------|-------------|---|---|
| MATERIAL: | / | SURFACE: | / |
| MAT. NO.: | 30020000051 | 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD | |
| STATUS: | / | Description: DPKF08A-F3-00A(H) | |
| APPD: | | DRAWING NO.: 30000359 | |
| CHKD: | | REV TO-1 | |
| DRAFT: | | SHEET 1/1 | |