



LOGO! 24CEO, LOGIC MODULE, WITHOUT DISPLAY, PU//O:
 24V/24V/24V TRANS., 8 DI (4AI)/4 DO; MEM 400 BLOCKS
 EXPANDABLE, ETHERNET BIULD IN WEB-SERVER, DATALOG
 STANDARD MICRO SD CARD FOR LOGO! SOFT COMFORT V8
 PREVIOS PROJECT USABEL

Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Time of day	
Time switching clocks	
• Number	190
• Power reserve	480 h
Digital inputs	
Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
Digital outputs	
Number of digital outputs	4; Transistor
Short-circuit protection	Yes; electrical (1 A)
Output current	
• for signal "1" permissible range for 0 to 55 °C, max.	0.3 A
EMC	
Emission of radio interference acc. to EN 55 011	
• Emission of radio interference acc. to EN 55 011 (limit class B)	Yes; Radio interference suppression according to EN55011, Limit Value Class B
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	
CSA approval	Yes

UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
acc. to VDE 0631	Yes

Marine approval	
• Marine approval	Yes

Ambient conditions	
Operating temperature	
• min.	0 °C
• max.	55 °C

Dimensions	
Width	71.5 mm
Height	90 mm
Depth	58 mm
last modified:	21.08.2014