

60X60X25 mm

JF0625-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS													
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
JF0625B1TR	Dual Ball	12	10.2 ~ 13.8	29.69	0.422	6000	0.37	4.44	0.38	42.5	60		
JF0625B1UR				26.96	0.357	5500	0.29	3.48	0.30	39.6			
JF0625-1S	B, S			24.27	0.292	5000	0.22	2.64	0.22	35.7			
JF0625-1H	B, S			21.44	0.237	4500	0.20	2.40	0.23	34.1			
JF0625-1M	B, S			19.00	0.185	4000	0.16	1.92	0.20	31.3			
JF0625-1L	B, S			16.76	0.145	3500	0.13	1.56	0.17	27.3			
JF0625-1E	B, S			14.24	0.108	3000	0.11	1.32	0.11	22.4			
JF0625-1V	B, S			11.72	0.076	2500	0.08	0.96	0.08	20.2			
JF0625B2TR	Dual Ball			24	20.4 ~ 27.6	29.69	0.422	6000	0.20	4.80		0.21	42.5
JF0625B2UR						26.96	0.357	5500	0.16	3.84		0.16	39.6
JF0625-2S	B, S					24.27	0.292	5000	0.13	3.12		0.14	35.7
JF0625-2H	B, S					21.44	0.237	4500	0.12	2.88		0.17	34.1
JF0625-2M	B, S	19.00	0.185			4000	0.11	2.64	0.13	31.3			
JF0625-2L	B, S	16.76	0.145			3500	0.10	2.40	0.12	27.3			
JF0625-2E	B, S	14.24	0.108			3000	0.07	1.68	0.07	22.4			
JF0625-2V	B, S	11.72	0.076			2500	0.06	1.44	0.06	20.2			
JF0625B4SR	Dual Ball	48	40.8 ~ 60.0			24.27	0.292	5000	0.09	4.32		0.09	35.7
JF0625B4HR	Dual Ball					21.44	0.237	4500	0.07	3.36		0.08	34.1
JF0625B4MR	Dual Ball					19.00	0.185	4000	0.06	2.88		0.07	31.3
JF0625B4LR	Dual Ball					16.76	0.145	3500	0.05	2.40		0.06	27.3

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

