

# End-product drawing

REV.	DESCRIPTION	DESIGN	DATE
XI	NEW DRAWING	PDH	2019/10/10

## NOTES:


1. MATERIAL: PA66、BRASS、 SILICONE;
2. CERTIFICATION: ROHS/cUL/TUV/SAA/CE;
3. FIRE-PROOT: UL94-V2.
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST: THE THREE ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY: 450V/20A  
 B、 TEST VOLTAGE: 2500V  
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0. 5-2. 5mm<sup>2</sup>  
 D、 OPERATING TEMPERATURE RANGE: -40~+105°C  
 E、 PROTECTION CLASS: IP68  
 SCREW CONNECTION



3 Pins




## Silicone parts



∅A	Wire OD
∅11.5	∅9-12mm
∅8.5	∅5-9mm

Weight	MEAS	Each carton number	G. W.
67.1g	42*30*34cm	250pcs	17.6Kg

UNLABELED TOLERANCE		
X. ±0.35	X.XX ±0.20	X.° ±2°
X.X ±0.25	X.XXX ±0.10	X.X° ±1°



UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	EW-M20T-3P
SCALE	1:1	CHKD		DWG NO	EW-M20T-3P
SHEET	1/1	APPD		TITLE	Waterproof connector