

Data sheet

Commercial Art.No.: 80.020.0004.0

Solid state relay WRS-SSAC1-250V6A

WRS-solid-state-relays, 1-phase, solid state relay not plugable, with LED, open module housing WEB 1002, dimensions: 12,5 x 80 mm (W xH), control voltage: 24 V DC, output 250V AC / 6A (Remark: the negative pole can be linked At the controll side with A jumper to the next module , if needed it has to be ordered seperately).



Commercial Art.No.	80.020.0004.0
EAN	4015573378438
Order Unit	5

Certificates / Approvals



Technical data

General

Modular version	No
-----------------	----

Technical data

Connection type	screw connection
Type of excitation	DC
Min. connection voltage	3 V
Max. connection voltage	60 V
Rated operating current AC-1	6 A
Rated operating current DC	5 A
Min. control voltage	24 V

Dimensions

Depth	59 mm
Width	12.5 mm
Height	80 mm

Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055

ETIM 4.0	EC002055
ETIM 3.0	EC002055

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1