



SPECIFICATION

Current Rating:3 Amp
 Voltage Rating:250V Max.
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Operation Temperature:-40°C~+105°C
 Insulator:PA66(UL-94HB)
 Contact:Brass,Selective Gold Plated Over Nickel
 RoHS Compliant

J H 6 - XX - H
 (1) (2) (3) (4) (5)

- (1) J:2.54mm Shunts(Jumper)
- (2) H:Handle Type
- (3) 6:Base Height
- (4) XX:Insulator Color
 Blank:Black
 BL:Blue
 RD:Red
 GR:Green
 WH:White
 YL:Yellow
- (5) H:RoHS Compliant

AUK A MEMBER OF AUK GROUP
太聯事業股份有限公司
AUK CONTRACTORS CO., LTD.

CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE 30~ ±0.30 20~30 ±0.3 10~20 ±0.3 5~10 ±0.3 0~5 ±0.2 ANG. ±1°
PART No. JH6-XX-H		MEI		
DRAWING No. JH6-XX-H		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		
REV.	NONE	UNIT mm	B0	

NO. REV.	BO	NEW RELEASE	HZF	05/17/2016
		REVISIONS	CHK	DATE