

# Data sheet

Commercial Art.No.: X6.031.4053.1

Connector RST20I3SXB1 ZR1 SW

RST20i3 connector with ATEX-authorization, 3 pole, female, screw connection, application 250V with PE, 20A, for cable diameters 6-10mm, coding color black, color of housing black



Commercial Art.No.	X6.031.4053.1
EAN	4049088011146
Order Unit	1

Certificates / Approvals

# SEV-Ex

# **Technical data**

## Classification

ECLASS 11	
ECLASS 8.1	27440605
ETIM 7.0	EC002560
ETIM 6.0	EC002560
ETIM 5.0	EC002560

#### General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
strain relief	yes
Pollution degree	3
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	black
Marking of poles	L, N, PE
Color of housing inclusive strain relief	black
Explosion-tested version	yes

#### Model

Model	female
Connection type	screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

#### Material

Housing material	Polyamide



halogen free	yes
Contact material	CuZn
Fire load	0.291 kWh
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

#### **Connection Data**

Cable diameter max.	10 mm
Cable diameter min.	6 mm
Connection cross section solid mm <sup>2</sup> max.	4 mm <sup>2</sup>
Connection cross section solid mm <sup>2</sup> min.	1.5 mm <sup>2</sup>
Connection cross section fine stranded mm <sup>2</sup> max.	4 mm <sup>2</sup>
Connection cross section fine stranded mm <sup>2</sup> min.	1.5 mm <sup>2</sup>
Terminations per pole	1
sheath strip length	26.5 mm
Wire strip length	8 mm

### Dimensions

Length	82 mm
Width	34.6 mm
Height	34.6 mm

### Note

Note	RST® terminals with screw clamping allow the connection of
	conductors without special preparation (without ferrules) according to
	EN 60999-1.

### Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

## Accessories

Commercial Art.No.:	Article-type description:	Description:
99.414.6205.2	Cover for female connector SW	RST20i3/2 cover piece, for covering unused female connectors, with fastening belt, color schwarz
Z5.564.4553.1	Cover for female connector SW	RST20i3/2 cover piece, for covering unused female connectors, color black

# Fits with

Commercial Art.No.:	Article-type description:	Description:
X6.030.0153.1	Distributor RST20I3VX3P1 F V SW	RST20i3 distribution block with ATEX-authorization, 3 pole, application 250V with PE, 20A, 1 input and 3 outputs, with fastening option, coding color black, color of housing black
X6.032.4053.1	Connector RST20I3SXS1 ZR1 V SW	RST20i3 connector with ATEX-authorization, 3 pole, male, screw connection, application 250V with PE, 20A, for cable diameters 6-10mm, coding color black, color of housing black



X6.032.5053.1	Device connector RST20I3S S1 M01V SW	RST20i3 device connector M25with ATEX-authorization, , 3 pole, male, screw connection, application 250V with PE, 20A, coding color black
X6.032.6053.1	Device connector RST20I3SXS1 M00V SW	RST20i3 device connector M20with ATEX-authorization, , 3 pole, male, screw connection, modular, application 250V with PE, 20A, coding color black, color of housing black