


P1	LEDK	P21	DB10
P2	LEDK	P22	DB9
P3	LEDA	P23	DB8
P4	LEDA	P24	DB7
P5	IMO	P25	DB6
P6	IM1	P26	DB5
P7	IM2	P27	DB4
P8	IM3	P28	DB3
P9	FMARK	P29	DB2
P10	VSYNC	P30	DB1
P11	HSYNC	P31	DB0
P12	DOTCLK	P32	IDVCC
P13	ENABLE	P33	CS
P14	DB17	P34	RS
P15	DB16	P35	WR/SCL
P16	DB15	P36	RD
P17	DB14	P37	RESET
P18	DB13	P38	SDI
P19	DB12	P39	VCC
P20	DB11	P40	GND



NOTES:

- OPERATING TEMPERATURE: -20°C TO 70°C
- STORAGE TEMPERATURE: -30°C TO 80°C
- DRIVE IC : R61505W
corresponding connector:XF2M-4015-1A
ROHS COMPLIANCY (环保标准)
GENERAL TOLERANCE:±0.2

CUSTOMER APVL	CUSTOMER	DATE	
DRAWN	SCALE	TITLE	
DFTG CHK	UNIT	MI0320ET-2	
ENGR CHK	mm	MODEL	
APPROVAL			
MULTI-INNO TECHNOLOGY CO.,LTD.		DWG NO	PAGE
			1/1