


Data sheet

Commercial Art.No.: 56.206.9355.0

Duo-ground block WTP 6/10 D1/2 PE

Ground terminal with push in connection for mounting on TS 35,nominal cross section: 10 mm²,Width: 8 mm,Color: Green-yellow



Commercial Art.No.	56.206.9355.0
EAN	4049088360596
Order Unit	100

Technical data

General

Nominal cross section	10 mm ²
Color	Green/yellow
Number of clamp positions per level	3
Width/grid dimension	8 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Mounting method	DIN rail (top hat rail)

Technical data

Rated voltage	1000 V
Rated impulse voltage	8 kV
Pollution degree	3
Closing plate required	yes
Type of insulation material	Thermoplastic
Length	77 mm

Connection Data

Connection type	Plug-in connection
Connection type 1	Plug-in connection
Minimum cross section solid	0.2 mm ²
Maximum cross section solid	10 mm ²
Minimum cross section fine stranded	0.2 mm ²
Maximum cross section fine stranded	10 mm ²
Minimum cross section stranded	0.2 mm ²
Maximum cross section stranded	10 mm ²
Minimum conductor cross section (flex., stranded) with cable end sleeve	0.2 mm ²
Maximum conductor cross section (flex., stranded) with cable end sleeve	10 mm ²
Wire strip length	15 mm

Cross section UL	10-8 AWG
Voltage UL	600 V
Cross section CSA	12-8 AWG
Voltage CSA	600 V

Note

Remark to rated voltage	in use with IVE WKFN 6-... rated voltage 800 V
-------------------------	--

Classification

ECLASS 11	
ECLASS 8.1	27141141
ETIM 7.0	EC000901
ETIM 6.0	EC000901
ETIM 5.0	EC000901
ETIM 4.0	EC000901
ETIM 3.0	EC000901

Product compliance

REACH-SVHC conformity status	Compliant
------------------------------	-----------