

## VICTORIA-IP-WWW

~90° wide beam. Ingress protected version.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 300.0 mm
Height	18.1 mm
Fastening	screw
Ingress protection classes	IP66, IP67
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
VICTORIA-WWW	Multi-lens	PMMA	clear	
VICTORIA-SEAL	Seal	Silicone	clear	
VICTORIA-O-RING	Seal	Silicone	milky	

### ORDERING INFORMATION:










Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CS16839_VICTORIA-IP-WWW » Box size: 343 x 343 x 298 mm	Multi-lens	34	34	34	9.1





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)


### PHOTOMETRIC DATA (MEASURED):

<p> <b>ELECTRIO</b>  <small>LED &amp; LIGHTING COMPANY</small></p> <p>LED: Victoria-PCB            FWHM / FWTM: 88.0° / 110.0°            Efficiency: 93 %            Peak intensity: 0.5 cd/m            LEDs/each optic: 2            Light colour: White            Required components:</p>		
<p><b>SAMSUNG</b></p> <p>LED: HiLOM HCF0 (LH181B)            FWHM / FWTM: 85.0° / 110.0°            Efficiency: 94 %            Peak intensity: 0.5 cd/m            LEDs/each optic: 1            Light colour: White            Required components:</p>		
<p><b>SAMSUNG</b></p> <p>LED: LH181B            FWHM / FWTM: 85.0° / 110.0°            Efficiency: 94 %            Peak intensity: 0.5 cd/m            LEDs/each optic: 1            Light colour: White            Required components:</p>		
<p><b>SAMSUNG</b></p> <p>LED: LH508A            FWHM / FWTM: 90.0° / 115.0°            Efficiency: 94 %            Peak intensity: 0.5 cd/m            LEDs/each optic: 1            Light colour: White            Required components:</p>		


#### PHOTOMETRIC DATA (SIMULATED):




LED J Series 2835  
 FWHM / FWTM 95.0° / 112.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED J Series 5050 Round LES  
 FWHM / FWTM 92.0° / 107.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON 2835 Line  
 FWHM / FWTM 95.0° / 117.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 2  
 Light colour White  
 Required components:







LED LUXEON 2835 Line  
 FWHM / FWTM 92.0° / 110.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:






### PHOTOMETRIC DATA (SIMULATED):

<p><b>NICHIA</b></p> <p>LED NFMW48xA            FWHM / FWTM 93.8° / 112.0°            Efficiency 91 %            Peak intensity 0.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris E 2835            FWHM / FWTM 94.0° / 111.0°            Efficiency 94 %            Peak intensity 0.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S8            FWHM / FWTM 94.0° / 112.0°            Efficiency 94 %            Peak intensity 0.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>SAMSUNG</b></p> <p>LED LH231B            FWHM / FWTM 94.0° / 111.0°            Efficiency 94 %            Peak intensity 0.5 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	

### PHOTOMETRIC DATA (SIMULATED):


#### SAMSUNG

LED LM28xB Series  
 FWHM / FWTM 95.0° / 111.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




SEOUL SEMICONDUCTOR

LED SEOUL DC 3528  
 FWHM / FWTM 94.0° / 114.0°  
 Efficiency 95 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEOUL SEMICONDUCTOR

LED SEOUL DC 3528  
 FWHM / FWTM 95.0° / 112.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)