

Data sheet

Commercial Art.No.: X6.032.4053.0

Connector RST20i3SXS1 ZR1 V GL

RST20i3 connector with ATEX-authorization, 3 pole, male, screw connection, application 250V with PE, 20A, for cable diameters 6-10mm, coding color light grey, color of housing light grey



Commercial Art.No.	X6.032.4053.0
EAN	4049088011313
Order Unit	1

Certificates / Approvals

SEV-Ex

Technical data

Classification

ECLASS 11	
ECLASS 8.1	27440605
ETIM 7.0	EC002560
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
strain relief	yes
Pollution degree	3
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	light grey
Marking of poles	L, N, PE
Color of housing inclusive strain relief	light grey
Explosion-tested version	yes

Model

Model	male
Connection type	screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
------------------	-----------

halogen free	yes
Contact material	CuZn
Fire load	0.268 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Connection Data

Cable diameter max.	10 mm
Cable diameter min.	6 mm
Connection cross section solid mm ² max.	4 mm ²
Connection cross section solid mm ² min.	1.5 mm ²
Connection cross section fine stranded mm ² max.	4 mm ²
Connection cross section fine stranded mm ² min.	1.5 mm ²
Terminations per pole	1
sheath strip length	26.5 mm
Wire strip length	8 mm

Dimensions

Length	79.1 mm
Width	34.6 mm
Height	34.6 mm

Note

Note	RST® terminals with screw clamping allow the connection of conductors without special preparation (without ferrules) according to EN 60999-1.
------	---

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

Accessories

Commercial Art.No.:	Article-type description:	Description:
05.564.4453.0	Cover for male connector GL	RST20i3/2 cover piece, for covering unused male connectors, color light grey
99.415.6205.2	Cover for male connector GL	RST20i3/2 cover piece, for covering unused male connectors, with fastening belt, color light grey

Fits with

Commercial Art.No.:	Article-type description:	Description:
X6.031.4053.0	Connector RST20i3SXB1 ZR1 GL	RST20i3 connector with ATEX-authorization, 3 pole, female, screw connection, application 250V with PE, 20A, for cable diameters 6-10mm, coding color light grey, color of housing light grey
X6.031.5053.0	Device connector RST20i3SXB1 M01 GL	RST20i3 device connector M25with ATEX-authorization, , 3 pole, female, screw connection, application 250V with PE, 20A, coding color light grey

X6.031.6053.0	Device connector RST20i3SXB1 M00 GL	RST20i3 device connector M20with ATEX-authorization, , 3 pole, female, screw connection, modular, application 250V with PE, 20A, coding color light grey, color of housing light grey
---------------	-------------------------------------	---