

## Data sheet

Commercial Art.No.: 81.000.6210.0

Fuse module 24V DC WIPOS FM 4-10

wipos FM 4-10, Fuse Module 24 V DC, for 4 fuses 5 x 20 mm, with general fault signal (N.O. contact), Mounting on DIN Rail TS35, supply with double clamp, LED status indication per fuse, max. 10A per fuse holder, total output current of 4 fuses: max. 40 A at 23°C, Operating voltage range: 18 - 30 V DC, W x H x D: 48 x 96 x 68 mm



Commercial Art.No.	81.000.6210.0
EAN	4049088116551
Order Unit	1

Certificates / Approvals



## Technical data

### General

Connection type	screw connection
Rail mounting possible	yes
Operating temperature min.	0 °C
Operating temperature max.	60 °C
Degree of protection (IP)	IP20

### Technical data

Fuse insert	G-fuse 5x20 mm
Rated fuse current, max.	10 A
Display	LED
General fault signal	potential-free semiconductor output
Switching output	18-30 V DC / max. 0,1 A
Connector cross section (input)	10 mm <sup>2</sup> solid/stranded
Connector cross section (output)	0.14 - 4 mm <sup>2</sup> solid / 0.14 - 2.5 mm <sup>2</sup> stranded

### Output

Type of output voltage	DC
Output voltage	24 V

### Input

Input voltage DC min.	24 V
Input voltage DC max.	24 V

Input current, max.	40 A
---------------------	------

**Dimensions**

Depth	68 mm
Width	48 mm
Height	96 mm

**Classification**

ECLASS 11	
ECLASS 8.1	27049002
ETIM 7.0	EC002540
ETIM 6.0	EC002540
ETIM 5.0	EC002540

**Product compliance**

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Hexahydromethylphthalic-anhydride; Lead
REACH-SVHC CAS numbers	25550-51-0; 7439-92-1