



IPC INTERFACE	
1	0001
2	0011
3	0012
4	0013
5	0014
6	0015
7	0016
8	0017
9	0018
10	0019
11	0020
12	0021
13	0022
14	0023
15	0024
16	0025
17	0026
18	0027
19	0028
20	0029
21	0030
22	0031
23	0032
24	0033
25	0034
26	0035
27	0036
28	0037
29	0038
30	0039
31	0040
32	0041
33	0042
34	0043
35	0044
36	0045
37	0046
38	0047
39	0048
40	0049
41	0050
42	0051
43	0052
44	0053
45	0054
46	0055
47	0056
48	0057
49	0058
50	0059

- NOTES:
1. DISPLAY TYPE: 2.0" TFT, TRANSMISSIVE, 6 O'CLOCK
 2. BACKLIGHT: 3 CHIP WHITE LED, (H=5mA/CONSTANT CURRENT)
 3. OPERATING TEMP: -20°C~70°C
 4. STORAGE TEMP: -30°C~60°C
 5. RESOLUTION: 176x320
 6. LCD IC: LI9225G
 7. 1. Preference dimension, 2. Critical dimension
 8. RoHS Compliant

REV	DATE	DESCRIPTION	STATUS	DATE	DIRECTION	BY	CHK	APPROVED
1.0	2015-03-24	Initial design						
1.1	2015-03-24	Final design						
2.0	2015-04-03	Initial design						

REV	DATE	DESCRIPTION	STATUS	DATE	DIRECTION	BY	CHK	APPROVED
1.0	2015-03-24	Initial design						
1.1	2015-03-24	Final design						
2.0	2015-04-03	Initial design						