

Data sheet

Commercial Art.No.: 70.350.4836.3

Hood EX GOT GG48 M32 09IA Z3

Hood revos Ex made of zinc, for single locking lever with trumpet glandM32 on the right side (IP54), low version, 48-poles explosion-tested version



Commercial Art.No.	70.350.4836.3
EAN	4015573775466
Order Unit	1

Certificates / Approvals



Technical data

General

Explosion-tested version	yes
Housing material	Die-cast zinc
Color	Blue
Degree of protection (IP)	IP54
Operating temperature range min.	-20 °C
Operating temperature range max.	60 °C

Model

Construction	48
Model of the housing	male
Locking mechanism	Single locking lever
Cable entry	Sideways
Type of cable	Gland nut
With cable screw gland	yes
Thread size M	32
Thread size PG	
EMC-version	No
Length	132 mm
Width	90 mm
Height	107 mm

Classification

ECLASS 11	
ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437
ETIM 5.0	EC000437

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(a); III-6(c)
REACH-SVHC conformity status	Duty-To-Declare

REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1