

## Data sheet

Commercial Art.No.: 25.303.4253.0

Panel header 8213 S / 12 DFLS

Feed Through-Pin Header, 12 -pole, with solder pin connection, without marking,  
pitch: 5,08 mm, series: 8214 S / 12 DFLS



Commercial Art.No.	25.303.4253.0
EAN	4015573316911
Order Unit	50

Certificates / Approvals



## Technical data

### General

Modular spacing	5.08 mm
Connection type	Soldering connection
Soldering process	None
Packaging	Carton
Number of poles	12
Number of levels	1
Marking	No
Fastening	Flange
Mating direction towards (circuit) board	None

### Technical data

Rated current	6.5 A
Overvoltage Category I	1000 V
Overvoltage Category II	400 V
Overvoltage Category III	250 V
Rated impulse voltage	4 kV

### Technical Data UL/CSA

Voltage UL	300 V
Current field wiring	8 A
Current factory wiring	8 A
Voltage CSA	300 V
Current CSA	8 A

### Other

Type of insulation material	Thermoplastic
Color	Grey
Height	17.5 mm
Length	81.28 mm
Depth	17.1 mm
Material contact base	CuSn

Material contact surface	Sn
--------------------------	----

**Classification**

ECLASS 11	
ECLASS 8.1	27440402
ETIM 7.0	EC002637
ETIM 6.0	EC002637
ETIM 5.0	EC002637
ETIM 4.0	EC002637

**Product compliance**

REACH-SVHC conformity status	Compliant
------------------------------	-----------

