

AN5279

Mono channel SEPP audio power amplifier IC

■ Overview


The AN5279 is a monolithic integrated circuit designed for 5.0 W (19 V, 8 Ω) output audio power amplifier. It is a mono channel SEPP IC suitable for TV application.

■ Features


- Few external components :
 - No Boucherot cells(output C, R)
 - No Bootstrap Capacitors
 - No Negative Feedback Capacitors
- Built-in muting circuit
- Built-in stand-by circuit
- Built-in various protection circuits
(Load-short, thermal, over-voltage and current)
- High ripple rejection(55 dB)
- Operating voltage range 10 V to 24 V(19 V typ.)

■ Applications

- TV



■ Block Diagram



■ Pin Descriptions

Pin No.	Descriptions	Pin No.	Descriptions
1	Ripple filter	6	Mute
2	Input GND	7	Output GND
3	Input	8	V _{CC}
4	Not connected	9	Standby
5	Output		

■ Absolute Maximum Ratings

Parameter	Symbol	Rating	Unit
Supply voltage	V _{CC}	26.0	V
Supply current	I _{CC}	1.6	A
Power dissipation ^{*2}	P _D	6.2	W
Operating ambient temperature ^{*1}	T _{opr}	−25 to +75	°C
Storage temperature ^{*1}	T _{stg}	−55 to +150	°C

Note) ^{*1} : Except these items, all other measurements are taken at T_a = 25 °C.

^{*2} : T_a = 75 °C with infinite heat sink.

■ Recommended Operating Range

Parameter	Symbol	Range	Unit
Supply voltage	V _{CC}	10.0 to 24.0	V

■ Electrical Characteristics at $V_{CC} = 19\text{ V}$, $f = 1\text{ kHz}$, $R_L = 8\ \Omega$, $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Quiescent current	I_{CQ}	$V_{IN} = 0\text{ mV}$	—	25	50	mA
Output end noise voltage *1	V_{NO}	No input, $R_g = 10\text{ k}\Omega$	—	0.22	0.4	mV
Voltage gain	G_V	$V_{IN} = 57\text{ mV}$	32	34	36	dB
Total harmonic distortion	THD	$V_{IN} = 57\text{ mV}$	—	0.2	0.4	%
Maximum Output Power	P_{O1}	$V_{CC} = 19\text{ V}$, THD = 10 %	4.0	5.0	—	W
Maximum Output power	P_{O2}	$V_{CC} = 22\text{ V}$, THD = 10 %	5.6	7.0	—	W
Ripple rejection ratio *1	RR	$V_r = 1\text{ V}_{rms}$ $f_r = 120\text{ Hz}$, $R_g = 10\text{ k}\Omega$	45	55	—	dB
Muting Ratio	MR	$V_{IN} = 57\text{ mV}$, $V_{MUTE} > 3.0\text{ V}$	70	80	—	dB
Muting control voltage	V_{MUTE}	$V_{IN} = 57\text{ mV}$, MR > 70 dB	3.0	—	—	V
Standby on voltage	V_{STD-ON}	No input, $I_{CC} \leq 0.1\text{ mA}$	—	—	5.0	V
Standby off voltage	$V_{STD-OFF}$	No input, $I_{CC} \geq 9.5\text{ mA}$	8.5	—	—	V

Note) *1 : For this measurement, use the 20 Hz to 20 kHz (12 dB/OCT) filter.


■ Terminal Equivalent Circuits

Pin No.	Equivalent circuit	Description	DC voltage (V)
1		<p>Ripple Filter</p> <p>This is the pin to connect the positive terminal of a ripple filter capacitor.</p>	$V_{CC} - 1.5V_{BE}$
2	—	<p>Input GND</p> <p>Input ground pin</p>	0
3		<p>Input</p> <p>This is the amplifier input pin.</p>	0
4	—	Not connected	—
5		<p>Output</p> <p>Output pin</p>	$V_{CC}/2$

■ Terminal Equivalent Circuits (continued)

Pin No.	Equivalent circuit	Description	DC voltage (V)
6		<p>Mute</p> <p>Mute input pin.</p> <p>Mute 'on' = 5 V</p> <p>Mute 'off' = 0 V</p>	—
7	—	<p>Output GND</p> <p>Output ground.</p>	0
8	—	<p>V_{CC}</p> <p>This is the power supply pin.</p>	19 V(typ.)
9		<p>Standby</p> <p>Standby control pin.</p> <p>Standby mode = 0 V</p> <p>Operational mode = V_{CC}</p>	—

■ Application Circuit Example




Operational mode	V_{CC}
Standby mode	0 V
Mute off	0 V
Mute on	5 V

■ Usage notes

- 1) External heatsink is needed when used. External heatsink should be fixed to the chassis.
- 2) Fin of the IC can be connected to GND.
- 3) Please prevent "Output to V_{CC} short", "Output to GND short" and "Reverse Insertion" to avoid damaging the IC.
- 4) The temperature protection circuit will operate at T_j around 150 °C. However, if temperature decreases, the protection circuit would automatically be deactivated and resume normal operation.

■ Technical Information

- $P_D - T_a$ curves of HSI P009-P-0000



Request for your special attention and precautions in using the technical information and semiconductors described in this material

- (1) An export permit needs to be obtained from the competent authorities of the Japanese Government if any of the products or technologies described in this material and controlled under the "Foreign Exchange and Foreign Trade Law" is to be exported or taken out of Japan.
- (2) The technical information described in this material is limited to showing representative characteristics and applied circuit examples of the products. It does not constitute the warranting of industrial property, the granting of relative rights, or the granting of any license.
- (3) The products described in this material are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this material are subject to change without notice for reasons of modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the guaranteed values, in particular those of maximum rating, the range of operating power supply voltage and heat radiation characteristics. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, redundant design is recommended, so that such equipment may not violate relevant laws or regulations because of the function of our products.
- (6) When using products for which dry packing is required, observe the conditions (including shelf life and after-unpacking standby time) agreed upon when specification sheets are individually exchanged.
- (7) No part of this material may be reprinted or reproduced by any means without written permission from our company.

Please read the following notes before using the datasheets

- A. These materials are intended as a reference to assist customers with the selection of Panasonic semiconductor products best suited to their applications.
Due to modification or other reasons, any information contained in this material, such as available product types, technical data, and so on, is subject to change without notice.
Customers are advised to contact our semiconductor sales office and obtain the latest information before starting precise technical research and/or purchasing activities.
- B. Panasonic is endeavoring to continually improve the quality and reliability of these materials but there is always the possibility that further rectifications will be required in the future. Therefore, Panasonic will not assume any liability for any damages arising from any errors etc. that may appear in this material.
- C. These materials are solely intended for a customer's individual use.
Therefore, without the prior written approval of Panasonic, any other use such as reproducing, selling, or distributing this material to a third party, via the Internet or in any other way, is prohibited.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.