



| 公差带/General Tolerances(mm) | |
|----------------------------|-------|
| 0 | >3 |
| ~ | >5 |
| 3 | ~ 10 |
| 6 | ~ 18 |
| 10 | ~ 30 |
| 18 | ~ 50 |
| 30 | ~ 80 |
| 50 | ~ 120 |
| 80 | ~ 180 |
| 120 | ~ 250 |
| 180 | ~ 315 |
| 250 | ~ 400 |
| 315 | ~ 500 |
| 400 | ~ 500 |
| 500 | ~ 500 |
| ±0.22 | ±0.26 |
| ±0.31 | ±0.37 |
| ±0.57 | ±0.80 |
| ±0.93 | ±1.05 |
| ±1.15 | ±1.60 |
| ±2.20 | ±2.50 |
| 0.1/10 | |
| ±Z | |

| | | | |
|-----------|--------------------|--------------|-----------------------|
| MATERIAL: | / | SURFACE: | / |
| MAT NO.: | / | | |
| STATUS: | / | | |
| APPD: | LI GL 2020.06.01 | NAME: | D-PC1.5-01P-1Y-00A(H) |
| CHKD: | Moo J 2020.06.01 | DRAWING NO.: | D-PC1.5-C01 |
| DRAFT: | Wang LX 2020.06.01 | TYPE: | CUSTOMER DRAWING |
| REV | EGN | DESCRIPTION | DRAFT |
| DATE | SIZE: A4 | SCALE: 2:1 | SHEET |
| 1 | 2 | 3 | 4 |
| 5 | 6 | 1/1 | |

| ITEM | NAME OF PART | MATERIAL | NOTES |
|--|--------------|----------|---------|
| 1 | Cover | PA66 | UL94V-0 |
| 使用温度范围/Operating Temperature(°C) -40~+105 | | | |
| 符合RoHS要求/Conform to RoHS | | | |
| 标准颜色编号/Standard color number: PANTONE / RAL | | | |

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

D-PC1.5-01P-1Y-00A(H)

1 2 3 4 5 6