

Data sheet

Commercial Art.No.: 80.020.6000.0

Solid state motor relay CEMOS-SSAC3-400V-2A

ceмос electronic controlled three-phase contactor, 3-phase, in A closed housing, dimensions (W x H x D) 45 x 75 x 110 mm voltage: 24 V AC/DC +10%/-15% output: 400 VAC / 2A motor power: 075 kW



Commercial Art.No.	80.020.6000.0
EAN	4015573457461
Order Unit	1

Technical data

General

Number of phases	3
Modular version	No

Technical data

Connection type	screw connection
Type of excitation	AC/DC
Min. connection voltage	100 V
Max. connection voltage	500 V
Min. control voltage frequency	50 Hz
Max. control voltage frequency	60 Hz
Rated operating current AC-1	2 A
Min. control voltage	24 V

Dimensions

Depth	110 mm
Width	45 mm
Height	75 mm

Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055

ETIM 4.0	EC002055
ETIM 3.0	EC002055

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Hexahydromethylphthalic-anhydride; Lead
REACH-SVHC CAS numbers	25550-51-0; 7439-92-1