


Data sheet

Commercial Art.No.: 80.020.2001.0

Solid state relay WRS-SSAC1-250V4A

WRS semiconductor relay, 1-phase, soldered semiconductor, with LED, open WEB 1002 housing, dimensions: 12.5 x 80 mm (WxH), control voltage: 24 V DC, output: 250 V AC/4 A



| | |
|--------------------|---------------|
| Commercial Art.No. | 80.020.2001.0 |
| EAN | 4015573322530 |
| Order Unit | 10 |

Certificates / Approvals



Technical data

General

| | |
|------------------|----|
| Number of phases | 1 |
| Modular version | No |

Technical data

| | |
|------------------------------|------------------|
| Connection type | screw connection |
| Type of excitation | DC |
| Min. connection voltage | 48 V |
| Max. connection voltage | 280 V |
| Rated operating current AC-1 | 4 A |
| Min. control voltage | 24 V |

Dimensions

| | |
|--------|---------|
| Depth | 56 mm |
| Width | 12.5 mm |
| Height | 80 mm |

Classification

| | |
|------------|----------|
| ECLASS 11 | |
| ECLASS 8.1 | 27371014 |
| ETIM 7.0 | EC002055 |
| ETIM 6.0 | EC002055 |
| ETIM 5.0 | EC002055 |
| ETIM 4.0 | EC002055 |
| ETIM 3.0 | EC002055 |

Product compliance

| | |
|------------------------------|--------------------|
| ROHS conformity status | Compliant/Exempted |
| ROHS exceptions | III-6(c) |
| REACH-SVHC conformity status | Duty-To-Declare |
| REACH-SVHC substances | Lead |

| |
|------------------------|
| REACH-SVHC CAS numbers |
|------------------------|

| |
|-----------|
| 7439-92-1 |
|-----------|