

精度等级/General	tolerance(mm)
0	>3
1	>6
2	>10
3	>18
4	>30
5	>50
6	>80
7	>120
8	>180
9	>280
10	>315
11	>400
12	>500
13	>630
14	>800
15	>1000

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	3000/10	/	3000/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/行架等	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	160/9	160/9	320/9
额定脉冲电压(V)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
线径范围(裸线和漆线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~1.5/26~16		
间距/Pitch(mm)/线径范围/Poles	3.81/N=02~24P		
引线长度/Stripping length(mm)	10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		


ITEM	NAME OF PART	MATERIAL	NOTES
7	Spring	Stainless steel	
6	Back Pin Header	Copper alloy	Sn Plated
5	Front Pin Header	Copper alloy	Sn Plated
4	Button	POM	UL94HB
3	Cover	PA66	UL94V-0
2	Housing	PA66	UL94V-0
1	Side Housing	PA66	UL94V-0

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	LI GL 2020.05.20
CHKD:	/
DRAFT:	MOEK 2017.03.01

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
DG246-3.81-XXP-1Y-00A(H)

DRAWING NO.:	DG246-3.81-C01
TYPE:	CUSTOMER DRAWING
SCALE:	2.5:1 SHEET
REV	T2
REV	1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				
4				
5				
6				



1 2 3 4 5 6