



未注公差/General tolerances(mm)										ϕ			
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	$\frac{\square}{\square}$
3	6	10	18	30	50	80	120	180	250	315	400	500	$\pm Z$
± 0.12	± 0.18	± 0.22	± 0.26	± 0.31	± 0.37	± 0.57	± 0.80	± 0.93	± 1.05	± 1.19	± 1.50	± 2.20	± 2.50

UL 标准/UL Standard:	B	C	D					
额定电压/电流/Rated Voltage(V)/Current(A)	300/30	/	300/10					
EC 标准/EC Standard:								
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	/	/					
额定电压/电流/Rated Voltage(V)/Current(A)	500/32	/	/					
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/					
螺栓扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43							
绞合范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4.0/26~10							
间距/Pitch(mm)	6.20							
剥线长度/Stripping length(mm)	7-8							
使用温度范围/Operating temperature(°C)	-40~+105							
符合RoHS环保要求/Conform to RoHS	Yes							
标准颜色编号/Standard color number:	/							
PANTONE / RAL								
SURFACE:								
MATERIAL:								
MAT NO.:								
 NINGBO DEGSON ELECTRICAL CO., LTD 宁波高松电子有限公司								
APPD:	NAME:							
CHKD:								
DRAFT:	DRAWING NO.:							
REV	ECN	DESCRIPTION	DRAFT	DATE	 TYPE:	SCALE:	REV	SHEET

1	2	3	4	5	6
---	---	---	---	---	---