



| | | 尺寸公差(mm) | | | |
|------------------------------------|----------------------|----------|-------|-------|-------------|
| | | 0 | >30 | >60 | >100 |
| Rated current | 15A | ~ | ~ | ~ | 0.05/10 |
| Rated voltage | 300V | 30 | 60 | 100 | ±T |
| Coil/Contact dielectric voltage | 2000V/S | ~ | ~ | ~ | >150 |
| Dielectric voltage between contact | 2000V/S | ±0.20 | ±0.30 | ±0.50 | ±0.70 ±1.00 |
| Screw torque | 1.0Nm | | | | |
| External connection wire | 20-14/0.5-2.5W | | | | |
| Ambient temperature | 5/100mm ² | | | | |
| Key controlled symbol | -45~+65℃ | | | | * |
| Conform to RoHS | | | | | |

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

REV ECN

DESCRIPTION

DRAFT DATE

NO.

SIZE: A4

TYPE: PRODUCT DRAWING

DRAWING NO.: 30000367

SCALE: 1:1

SHEET

REV

TO-1

1/1

| NO. | DESCRIPTION | MATERIAL NO. | QTY | MATERIAL | NOTES |
|-----|---------------------|--------------|-----|----------|-------|
| 1 | DSRT05A-E3-00A(H)-N | 300190000130 | 1 | | |

MATERIAL: / SURFACE: /

MAT NO.: 300200000059

STATUS: /

APPD: /

CHKD: /

DRAFT: /

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DSRT05A-E3-00A(H)