

DC FAN

JAMICON®

120X120X25 mm

JF1225-00 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1225B1UR00	Dual Ball	12	10.2 ~ 13.8	100.50	0.269	3000	0.50	6.00	0.50	45.7	135
JF1225B1SR00				89.87	0.224	2700	0.37	4.44	0.37	42.8	
JF1225B1H-00				80.11	0.186	2400	0.25	3.00	0.30	39.5	
JF1225B1M-00				69.57	0.147	2100	0.19	2.28	0.25	36.3	
JF1225B1L-00				59.57	0.111	1800	0.14	1.68	0.20	32.4	
JF1225B1E-00				47.88	0.078	1500	0.10	1.20	0.12	27.4	
JF1225S1H-00	Sleeve	12	10.2 ~ 13.8	80.11	0.186	2400	0.25	3.00	0.30	39.5	
JF1225S1M-00				69.57	0.147	2100	0.20	2.40	0.25	36.3	
JF1225S1L-00				59.57	0.111	1800	0.14	1.68	0.20	32.4	
JF1225S1E-00				47.88	0.078	1500	0.10	1.20	0.12	27.4	
JF1225B2UR00	Dual Ball	24	20.4~27.6	100.50	0.269	3000	0.28	6.72	0.28	45.7	
JF1225B2SR00				89.87	0.224	2700	0.21	5.04	0.21	42.8	
JF1225B2H-00				80.11	0.186	2400	0.20	4.80	0.25	39.5	
JF1225B2M-00				69.57	0.147	2100	0.14	3.36	0.20	36.3	
JF1225B2L-00				59.57	0.111	1800	0.11	2.64	0.15	32.4	
JF1225B2E-00				47.88	0.078	1500	0.08	1.92	0.10	27.4	
JF1225S2H-00	Sleeve	24	20.4~27.6	80.11	0.186	2400	0.20	4.80	0.25	39.5	
JF1225S2M-00				69.57	0.147	2100	0.14	3.36	0.20	36.3	
JF1225S2L-00				59.57	0.111	1800	0.11	2.64	0.15	32.4	
JF1225S2E-00				47.88	0.078	1500	0.08	1.92	0.10	27.4	
JF1225B4U-00	Dual Ball	48	40.8 ~ 60.0	100.50	0.269	3000	0.14	6.72	0.14	45.7	
JF1225B4S-00				89.87	0.224	2700	0.12	5.76	0.12	42.8	
JF1225B4H-00				80.11	0.186	2400	0.10	4.80	0.10	39.5	
JF1225B4M-00				69.57	0.147	2100	0.08	3.84	0.08	36.3	
JF1225B4L-00				59.57	0.111	1800	0.07	3.36	0.07	32.4	
JF1225B4E-00				47.88	0.078	1500	0.06	2.88	0.06	27.4	

Specifications subject to change without notice

