

1. MATERIAL: PA66、BRASS、 SILICONE;
2. CERTIFICATION:ROHS/TUV/SAA/CE;
3. FIRE-PROOT:UL94-V2。
4. NO DEFECT IN APPEARANCE;
5. UNITS: mm;
6. CONDUCTION TEST:THE TWO ENDS OF THE 3 CORE JOINTS ARE RESPECTIVELY CONNECTED
7. A、 MAXIMUM CURRENT-CARRYING CAPACITY:400V/40A
 B、 TEST VOLTAGE: 2500V
 C、 SUITABLE FOR CABLES CROSS SECTIONS: 0.5-6mm²
 D、 OPERATING TEMPERATURE RANGE: -40~+105℃
 E、 PROTECTION CLASS: IP68



3 Pins



M32 Silicone parts	M25 Silicone parts																		
<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Silicone</th> <th>Wire OD</th> </tr> </thead> <tbody> <tr> <td>One Hole</td> <td>∅14-18mm</td> </tr> <tr> <td>2 holes</td> <td>∅5.5-8.5mm</td> </tr> <tr> <td>3 holes</td> <td>∅5-8mm</td> </tr> <tr> <td>4 holes</td> <td>∅3.5-6.5mm</td> </tr> </tbody> </table>	Silicone	Wire OD	One Hole	∅14-18mm	2 holes	∅5.5-8.5mm	3 holes	∅5-8mm	4 holes	∅3.5-6.5mm	<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>∅A</th> <th>Wire OD</th> </tr> </thead> <tbody> <tr> <td>∅14</td> <td>∅10-14mm</td> </tr> <tr> <td>∅12</td> <td>∅9-12mm</td> </tr> <tr> <td>∅8.5</td> <td>∅5-9mm</td> </tr> </tbody> </table>	∅A	Wire OD	∅14	∅10-14mm	∅12	∅9-12mm	∅8.5	∅5-9mm
Silicone	Wire OD																		
One Hole	∅14-18mm																		
2 holes	∅5.5-8.5mm																		
3 holes	∅5-8mm																		
4 holes	∅3.5-6.5mm																		
∅A	Wire OD																		
∅14	∅10-14mm																		
∅12	∅9-12mm																		
∅8.5	∅5-9mm																		



Item#	Silicone	Weight	MEAS	Each carton number	G. W.
EW-M25-3PB-2T	M32 with one hole	63.1g	42*30*34cm	250pcs	16.6Kg
EW-M25-3PB-3T	M32 1 in 2 out	65.3g			17.2Kg
EW-M25-3PB-4T	M32 1 in 3 out	64.6g			17Kg
EW-M25-3PB-5T	M32 1 in 4 out	64.9g			17.1Kg

UNLABELED TOLERANCE					UNITS	mm	DRAW	PDH 2019/10/10	PART NO.	EW-M25-3PB	FUCON	
X.	±0.35	X.XX	±0.20		X.°	±2°	SCALE	1:1	CHKD	DWG NO		EW-M25-3PB
X.X	±0.25	X.XXX	±0.10		X.X°	±1°	SHEET	1/1	APPD	TITLE		Waterproof connetor