

## Data sheet

Commercial Art.No.: 80.010.4103.0

Relay module FLARE-24DC-2W-250V6A-F

flare, mechanical relays with 12,4 mm overall width, output, 2 change-over contact, spring clamp terminal, input: 24 V DC, output: 2 50V AC / 6A, voltage / current minimum: 24V / 8mA, jumper At negative pole At the controll side , type: flare-24VDC-2W-250V6A-F



Commercial Art.No.	80.010.4103.0
EAN	4015573568723
Order Unit	5

Certificates / Approvals



**CAN-Ex**



## Technical data

### General

Connection type	spring clamp connection
Number of change-over contacts	2
Detachable clamps	No
Drive, polarization	Polarity free
Drive, function	Mono stable
Forced-guided contacts	No
Complete with socket	yes
Degree of protection (IP)	IP20

### Technical data

Type of excitation	DC
Min. nominal voltage DC	24 V
Lower nominal voltage DC	19.2 V
Upper nominal voltage DC	30 V

### Dimensions

Depth	70 mm
Width	12.4 mm
Height	98 mm

### Classification

ECLASS 11	
-----------	--

ECLASS 8.1	27371601
ETIM 7.0	EC001437
ETIM 6.0	EC001437
ETIM 5.0	EC001437
ETIM 4.0	EC001437
ETIM 3.0	EC001437

**Product compliance**

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant