

Data sheet

Commercial Art.No.: 57.904.4655.0

Compensating terminal 9785U/1 KOHM-SPT/V0

Compensating terminal block with screw connection for mounting on TS 35 and TS 32, nominal cross section 4 mm², width 12 mm, color g ray



| | |
|--------------------|---------------|
| Commercial Art.No. | 57.904.4655.0 |
| EAN | 4015573605688 |
| Order Unit | 50 |

Technical data

General

| | |
|--|--------------------------------|
| Nominal cross section | 2.5 mm ² |
| Color | Grey |
| Number of levels | 2 |
| Number of clamp positions per level | 2 |
| Width/grid dimension | 12 mm |
| Insulating housing | PA666 |
| Inflammability class of insulation material acc. with UL94 | V0 |
| Mounting method | DIN rail (top hat rail)/G-rail |
| Terminal blocks for electrical installations | No |
| Type of component | Potenzimeter |

Technical data

| | |
|-----------------------------|---------------|
| Pollution degree | 3 |
| Closing plate required | No |
| Type of insulation material | Thermoplastic |
| Length | 49 mm |

Connection Data

| | |
|-------------------------------------|---------------------|
| Connection type 1 | screw connection |
| Connection type 2 | screw connection |
| Minimum cross section solid | 0.5 mm ² |
| Maximum cross section solid | 2.5 mm ² |
| Minimum cross section fine stranded | 0.5 mm ² |
| Maximum cross section fine stranded | 2.5 mm ² |
| Wire strip length | 9 mm |
| Torque conductor mounting | 0.5 Nm |

Classification

| | |
|------------|----------|
| ECLASS 11 | |
| ECLASS 8.1 | 27141127 |
| ETIM 7.0 | EC000903 |
| ETIM 6.0 | EC000903 |
| ETIM 5.0 | EC000903 |
| ETIM 4.0 | EC000903 |

| | |
|----------|----------|
| ETIM 3.0 | EC000903 |
|----------|----------|

Product compliance

| | |
|------------------------------|--------------------|
| ROHS conformity status | Compliant/Exempted |
| ROHS exceptions | III-6(c) |
| REACH-SVHC conformity status | Duty-To-Declare |
| REACH-SVHC substances | Lead |
| REACH-SVHC CAS numbers | 7439-92-1 |