

Data sheet

Commercial Art.No.: X6.052.4153.1

Connector RST20i5XS1 ZR2 V SW

RST20i5 connector with ATEX-authorization, 5 pole, male, screw connection, application 250/400V with PE, 20A, for cable diameters 10-14mm, coding color black, color of housing black



Commercial Art.No.	X6.052.4153.1
EAN	4049088009709
Order Unit	1

Certificates / Approvals

SEV-Ex

Technical data

Classification

ECLASS 11	
ECLASS 8.1	27440605
ETIM 7.0	EC002560
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560

General

Rated current	20 A
Rated voltage	250 V / 400 V
Rated impulse voltage	4 kV
strain relief	yes
Pollution degree	3
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	black
Marking of poles	1, 2, 3, N, PE
Color of housing inclusive strain relief	black
Explosion-tested version	yes

Model

Model	male
Connection type	screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

Material

Housing material	Polyamide
------------------	-----------

halogen free	yes
Contact material	CuZn
Fire load	0.285 kWh
Insulation components continuous temperature	100 °C
Surface finish	Silver-plated

Connection Data

Cable diameter max.	14 mm
Cable diameter min.	10 mm
Connection cross section solid mm ² max.	2.5 mm ²
Connection cross section solid mm ² min.	1.5 mm ²
Connection cross section fine stranded mm ² max.	2.5 mm ²
Connection cross section fine stranded mm ² min.	1.5 mm ²
Terminations per pole	1
sheath strip length	26.5 mm
Wire strip length	8 mm

Dimensions

Length	78.4 mm
Width	34.6 mm
Height	34.6 mm

Note

Note	fine-stranded and stranded wires have to be used without ferrules
------	---

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

Accessories

Commercial Art.No.:	Article-type description:	Description:
05.565.9953.1	Cover for male connector SW	RST20i5/4 cover piece, for covering unused male connectors, color black
99.532.0000.7	Cover for male connector SW	RST20i5/4 cover piece, for covering unused male connectors, with fastening belt, color black

Fits with

Commercial Art.No.:	Article-type description:	Description:
X6.051.4153.1	Connector RST20i5SXB1 ZR2 SW	RST20i5 connector with ATEX-authorization, 5 pole, female, screw connection, application 250/400V with PE, 20A, for cable diameters 10-14mm, coding color black, color of housing black
X6.051.5053.1	Device connector RST20i5SXB1 M01 SW	RST20i5 device connector M25with ATEX-authorization, , 5 pole, female, screw connection, application 250/400V with PE, 20A, coding color black

X6.051.6053.1	Device connector RST20I5SXB1 M00 SW	RST20i5 device connector M20with ATEX-authorization, , 5 pole, female, screw connection, modular, application 250/400V with PE, 20A, coding color black, color of housing black
X6.053.6053.1	Device connector RST20I5SXB1 M90 SW	RST20i5 device connector (90° angled) M20with ATEX-authorization, , 5 pole, female, screw connection, modular, application 250/400V with PE, 20A, coding color black, color of housing black