


Cell(电芯):	LP303248	Date code(喷码):	Inner controlling standard(内控标准)	
	Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	380	*PCM protection (保护板参数)	Overcurrent Detection(A) (过流值)
Battery Specification (电池参数)	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single battery capacity (单体电池容量)	400	Overcharge Detection Voltage(V) (过充电保护电压)	4.28±0.05
	Nominal Voltage 标称电压 (V)	3.7	Overdischarge Detection Voltage(V) (过放电保护电压)	2.3±0.1
Internal impedance 内阻 (≦)	(mΩ, AC 1KHZ)	250	Charge Temp. 充电温度 (°C)	0-45
			Discharge Temp. 放电温度 (°C)	-20-60
			Humidity(湿度)	65±20%

Remark(备注):

- No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
- RoHS compliant(严格按照ROHS要求生产).



Title	LP303248-PCM-LD	Drawn:	Moyongdi	Revise No.:	E4-2009
File NO.	A01690	Checked 1:	Jane	Projection:	
		Checked 2:	Keyan	Page:	1/1
		Approved:		Scale:	2 : 1
		Draw Date:	2010/03/02	Unit:	mm