


## Data sheet

Commercial Art.No.: 80.020.2001.0

Solid state relay WRS-SSAC1-250V4A

WRS semiconductor relay, 1-phase, soldered semiconductor, with LED, open WEB 1002 housing, dimensions: 12.5 x 80 mm (WxH), control voltage: 24 V DC, output: 250 V AC/4 A



Commercial Art.No.	80.020.2001.0
EAN	4015573322530
Order Unit	10

Certificates / Approvals



## Technical data

### General

Number of phases	1
Modular version	No

### Technical data

Connection type	screw connection
Type of excitation	DC
Min. connection voltage	48 V
Max. connection voltage	280 V
Rated operating current AC-1	4 A
Min. control voltage	24 V

### Dimensions

Depth	56 mm
Width	12.5 mm
Height	80 mm

### Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055
ETIM 4.0	EC002055
ETIM 3.0	EC002055

### Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead

REACH-SVHC CAS numbers
------------------------

7439-92-1
-----------