



		尺寸公差(mm)			
		0	>30	>60	>100
Rated current	300V/A	~	~	~	~
Rated voltage	300V	30	60	100	150
Coil/Contact dielectric voltage	2000V/S	~	~	~	>150
Dielectric voltage between contact	2000V/S	±0.20	±0.30	±0.50	±0.70 ±1.00
Screw torque	1.0Nm				
External connection wire	20-14/0.5-2.5W				
Ambient temperature	G/mm ²				
Key controlled symbol	-40~+65℃				*
Conform to RoHS					

Printing for laser marking/printing content is clear ,no broken line/rect
Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE

1	DPYF14A-E3-00A(H)-N	30019000029	1		
MATERIAL: /		SURFACE: /			
MAT. NO.: 30020000048					
STATUS: /					
APPD: /		Description: DEGSON ® NINGBO DEGSON ELECTRICAL CO., LTD			
CHKD: /		DPYF14A-E3-00A(H)			
DRAFT: /		DRAWING NO.: 30000356		REV	TO-1
SIZE: A4		TYPE: PRODUCT DRAWING		SCALE: 1:1	SHEET 1/1

D

C

B

A

1 2 3 4 5 6