

PRODUCT DETAILS

Model	Voltage (V)	Current (A)	Power (W)	Air Volum (CFM)	Speed (Rpm)	Noise Level (db)	Weight (G)
RQD4010LS	5	0.08	0.40	4.70	4200	14.0	14
RQD4010MS	5	0.11	0.55	5.70	4800	20.0	14
RQD4010HS	5	0.19	0.95	6.70	6000	25.0	14
RQD4010LS	12	0.07	0.84	4.70	4200	14.0	14
RQD4010MS	12	0.08	0.96	5.70	4800	20.0	14
RQD4010HS	12	0.10	1.20	6.70	6000	25.0	14
RQD4010LS	24	0.07	1.68	4.70	4200	14.0	14
RQD4010MS	24	0.08	1.92	5.70	4800	20.0	14
RQD4010HS	24	0.09	2.16	6.70	6000	25.0	14

General description of the:

Each of the fans has DC brushless motor for driving, a tubular frame and plastic impeller. they have some superior features such as large air volume, low noise ,low EMI, low power consumption, high efficiency and long life etc. they are specially used in computer system. office automation products, and automatic applications on the ground for air cooling and venting where there is a DC power supply.

Application cond itons:

Temperature Range(°C):-20°C+60°CBall Bearing(B) -20°C+40°C Sleeve Bearing(S);

Humidity permissible(%):≤90%(25°C);

Atmospheric Pressure 55kpa;

Vibration Permissible: Frequency 10Hz,Double Amplitude 1.5mm;

Impact Permissible: (peak acceleration)40m/ S²

ILLustration Of The Code:

