

Data sheet

Commercial Art.No.: 81.000.6135.0

Switched-mode power supply WIPOS P1 24-3.8

wipos switched-mode power supply, nominal voltage: 24 V DC / 3,8A (setting range 22,5-24,5 V DC), sustained short-circuitprotection, input voltage range: 115 V AC / 230 V AC; 210-370 V DC,single phase, W x H x D: 63,2 × 123,6 × 123,6 mm



Commercial Art.No.	81.000.6135.0
EAN	4049088037474
Order Unit	1

Certificates / Approvals



Technical data

General

Connection type	screw connection
Number of phases	Single phase power supply
Modular version	No
Mounting type, other	No
Mounting type, wall mounting	No
Rail mounting possible	yes
Housing material	Metal
Operating temperature min.	-35 °C
Operating temperature max.	71 °C
relative humidity min.	20 %
relative humidity max.	95 %
Storage temperature / transport min.	85 °C
Storage temperature / transport max.	-40 °C
Degree of protection (IP)	IP20
Parallel-service possible	No

Technical data

Function display	"DC OK" (LED green) (U(o) 17.6...19.4V)
function display "DC Low"	"DC Low" (LED red)
Short-circuit protective device	Strombegrenzung (fold forward)
temperature coefficient	±0,03%/K
ripple and noise	< 0.05 V
hold time 115V AC	> 25 ms

hold time 230V AC	> 30 ms
isolating voltage Output DC	4242 V
cohesive resistance (In-/Output)	100 MOhm
Derating	61°C...71°C: 2,5 %/K
cooling	free convection
MTBF	486.000h
Connector cross section (input)	min. 0,5mm ² (AWG24) max. 6mm ² (AWG10)
Connector cross section (output)	min. 0,5mm ² (AWG24) max. 6mm ² (AWG10)
Wire strip length	8 mm
Permissible torque max.	0.6 Nm
CE-Norm	EN55022 & EN61000-6-3, EN61000-3-2, EN61000-3-3, EN55024 & EN61000-6-2, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11, EN60204-1, EN61204-3
TÜV/safety	EN60950-1, EN61558-1, EN61558-2-16(erfüllt EN60204) , IIRAM
Approval cULus	UL 508 Listed, UL60950-1 Recognized UL 1310 Class 2 Power supply
Number of +	2
Number of -	2
Further terminals	L1, N, PE, OK (2x Relay-NO)

Output

Type of output voltage	DC
Power output	108 W
Output voltage stabilized	yes
Output voltage	24 V
Min. output voltage	22.5 V
Max. output voltage	28.5 V
Output current	3.8 A

Input

Type of voltage (input voltage)	
Power consumption	< 130 VA
Input voltage DC min.	210 V
Input voltage DC max.	375 V
Input voltage AC min.	115 V
Input voltage AC max.	230 V
Rated frequency min.	47 Hz
Rated frequency max.	63 Hz
Input fuse	T3, 15A / 250V (internal)

Dimensions

Depth	123.6 mm
Width	63.2 mm
Height	123.6 mm
Mounting Distance horizontal	25 mm
Mounting Distance vertical	25 mm
Weight	920 g

Classification



ECLASS 11	
ECLASS 8.1	27049002
ETIM 7.0	EC002540

ETIM 6.0	EC002540
ETIM 5.0	EC002540

Product compliance

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant

00 - PEE 12/92



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Die Reproduktion, Distribution und Utilization of this document as well as the communication of its contents to others without express authorization is prohibited.

Weitere Daten siehe KATALOG oder eKatalog.
Additional data see CATALOG or e-Catalog.

www.wieland-electric.com
e-shop.wieland-electric.com

ja/yes Stoffverbots- und Deklarationsliste nach UU-TQM-05/03 ist einzuhalten.
Conformity with Wieland document UU-TQM-05/03 (list of prohibited / declarable hazardous substances) to be declared!

Freitoleranz nach General tolerance		CAD-Zeichnung, keine manuellen Änderungen CAD-Drawing, no manual modifications allowed		1. Verwendung: First Use: *		Blatt: Sheet: *	
		Werkstoff/ Material		2014	Tag/ Date	Name	Zeichnung Nr./ Drawing No. 81.000.6135.0 01K
Maßstab/Scale				gezeichnet drawn	26.02.	Kötzner	
				geprüft checked			Maße in mm/Dimensions are in mm
				Normgepr. Stand. check			
Datei/ File: 028941_A_01K.DCD		Ersatz für/ Replacement for:					
		Type		Benennung/ Title			
				Schaltnetzteil / Switching Power Supply wipos P1 24 V DC / 3.8 A 1PH			
Index	Datum/ Blatt Date/ Sheet						
Änderung/ Revision							

810006135001K_2 CADW3072 Koetzner 2014-02-26T13:17:27 1.000