


Data sheet

Commercial Art.No.: 90.230.1020.2

Cable assembly GST08i2BS 75T 10WS

GST08i2 connection cable female - male, length 1.0 m, 2 pole, coding protection class II 250 V, 2.5 A, coding color white, cable color white, cross section 0.75 mm², cable type H03V2V2H2-F



Commercial Art.No.	90.230.1020.2
EAN	4049088364983
Order Unit	1

Certificates / Approvals



Technical data

General

Rated current	2.5 A
Rated voltage	250 V
Mechanical coding	Code 1
Lockable	No
Color of coding/ contact carrier	white
Color of housing inclusive strain relief	white

Model

Nominal cross section conductor	0.75 mm ²
Degree of protection (IP)	IP20
Cable type	H03V2V2H2-F
Cable color	white
Cable diameter min.	3.5 mm
Cable diameter max.	5.4 mm
Version of cable	female - male
Type of cord set	connecting cable
Version cable end 1	GST08i2 socket
Version cable end 2	GST08i2 plug

Material

halogen free	No
Continuous temperature of cable	90 °C
Insulation components continuous temperature	90 °C
Fire load	0 kWh

Dimensions

Total length	1 m
--------------	-----

Classification

ECLASS 11	
-----------	--

ECLASS 8.1	27440604
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

Product compliance

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant

Fits with

Commercial Art.No.:	Article-type description:	Description:
90.230.0523.2	Cable assembly GST08I2B- 75T 05WS	GST08i2 extension cable female - free end, length 0.5 m, 2 pole, coding protection class II 250 V, 2.5 A, coding color white, cable color white, cross section 0.75 mm ² , cable type H03V2V2H2-F
90.230.0524.2	Cable assembly GST08I2-S 75T 05WS	GST08i2 extension cable male - free end, length 0.5 m, 2 pole, coding protection class II 250 V, 2.5 A, coding color white, cable color white, cross section 0.75 mm ² , cable type H03V2V2H2-F
90.230.2024.2	Cable assembly GST08I2-S B75T 20WS	GST08i2 extension cable male - free end, length 2.0 m, 2 pole, coding protection class II 250 V, 2.5 A, coding color white, cable color white, cross section 0.75 mm ² , cable type H03V2V2H2-F