

DC AXIAL FAN

JAMICON®

25x25x10 mm

KF0210-02 Series

- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±15%



SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)		
KF0210B5HR	Dual Ball	5	4.25~5.75	2.57	0.288	13000	0.20	1.00	1.0	27.40	7		
KF0210B5MR				1.96	0.176	10000	0.13	0.65	0.8	22.40			
KF0210B5LR				1.29	0.090	7000	0.10	0.50	0.5	14.80			
KF0210C5HR	Ball + Sleeve			2.57	0.288	13000	0.20	1.00	1.0	27.40			
KF0210C5MR				1.96	0.176	10000	0.13	0.65	0.8	22.40			
KF0210C5LR				1.29	0.090	7000	0.10	0.50	0.5	14.80			
KF0210S5HR	Sleeve			2.57	0.288	13000	0.22	1.10	1.1	27.40			
KF0210S5MR				1.96	0.176	10000	0.18	0.90	1.0	22.40			
KF0210S5LR				1.29	0.090	7000	0.12	0.60	0.7	14.80			
KF0210B1HR	Dual Ball			12	10.2~13.8	2.57	0.288	13000	0.09	1.08		1.6	27.40
KF0210B1MR						1.96	0.176	10000	0.07	0.84		0.8	22.40
KF0210B1LR						1.29	0.090	7000	0.06	0.72		0.7	14.80
KF0210C1HR	Ball + Sleeve	2.57	0.288			13000	0.12	1.44	1.4	27.40			
KF0210C1MR		1.96	0.176			10000	0.07	0.84	0.8	22.40			
KF0210C1LR		1.29	0.090			7000	0.06	0.72	0.7	14.80			
KF0210S1HR	Sleeve	2.57	0.288			13000	0.12	1.44	1.5	27.40			
KF0210S1MR		1.96	0.176			10000	0.10	1.20	1.3	22.40			
KF0210S1LR		1.29	0.090			7000	0.08	0.96	1.2	14.80			

Specifications subject to change without notice

