

## Data sheet

Commercial Art.No.: 70.344.4836.4

Bottom EX GUT GR48 M40 09IA Z4

Bottom-base revos Ex made of zinc, with single locking lever and cable gland with bend protection and strain relief M40 on the left side, with protective cover (IP54), low version, 48-polig, explosion-tested version



Commercial Art.No.	70.344.4836.4
EAN	4015573740501
Order Unit	1

Certificates / Approvals



## Technical data

### General

Housing material	Die-cast zinc
Color	Blue
Surface	With powder coating
Operating temperature range min.	-20 °C
Operating temperature range max.	60 °C

### Model

Construction	48
Model of the housing	female
Locking mechanism	Single locking lever
Cable entry	Sideways
Type of cable	Gland nut
With cable screw gland	yes
Thread size M	40
Thread size PG	
EMC-version	No
Length	146 mm
Width	120 mm
Height	117 mm

### Classification

ECLASS 11	
-----------	--

ECLASS 8.1	27440202
ETIM 7.0	EC000437
ETIM 6.0	EC000437

**Product compliance**

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1