



尺寸公差(mm)				0.05/10 ±IT
0	>30	>60	>100	
±0.20	±0.30	±0.50	±0.70	±1.00

Rated current	10A
Rated voltage	300V
Coil/Contact dielectric voltage	4000V/S
Dielectric voltage between contact	2500V/S
Screw torque	1.0Nm
External connection wire	20-14/0.5-2.5W G/mm ²
Ambient temperature	-45~+85℃
Key controlled symbol	*
Conform to RoHS	
Printing for laser marking/printing content is clear ,no broken line,ect	
Seal literal reference according to the foot position in the drawing	

NO.	DESCRIPTION	MATERIAL NO.	QTY	MATERIAL	NOTES
2	B-35A-00A(H)	30070000089	1		
1	DPKF14A-F3-00A(H)-N	30019000033	1		

MATERIAL:	SURFACE: /	
MAT.NO.:	30020000052	宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
STATUS:	/	
APPD:	Description:	
CHKD:	DPKF14A-F3-00A(H)	
DRFT:	/	
DRAWING NO.:		30000360
REV	TO-1	
SIZE: A4	TYPE: PRODUCT DRAWING	SCALE: 1:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 本文件及其中所载之内容，未经本公司事先书面许可，不得擅自复制或传播。如有违反，本公司将依法追究法律责任。所有权利保留，包括专利、实用新型或外观设计注册在内。