

# Data sheet

Commercial Art.No.: 96.021.4253.0

Connector RST20I2S B13ZRX GL

RST20i3/2 splitter connector, 2 pole, female, screw connection, application 250V, 20A, for cable diameters 6-10mm, coding color light grey, color of housing light grey



Commercial Art.No.	96.021.4253.0
EAN	4015573895027
Order Unit	1

Certificates / Approvals



CHARGE STREET



LR RINA



## **Technical data**

General

Rated current	20 A
Rated voltage	250 V
Rated impulse voltage	4 kV
strain relief	yes
Pollution degree	3
Lockable	self-locking (unlocking by tool)
Color of coding/ contact carrier	light grey
Marking of poles	L, N
Color of housing inclusive strain relief	light grey

#### **Connection Data**

Cable diameter max.	10 mm
Cable diameter min.	6 mm
Connection cross section solid mm <sup>2</sup> max.	6 mm²
Connection cross section solid mm <sup>2</sup> min.	0.75 mm²
Connection cross section solid AWG min.	16 AWG
Connection cross section solid AWG max.	10 AWG
Connection cross section fine stranded mm <sup>2</sup> max.	6 mm²
Connection cross section fine stranded mm <sup>2</sup> min.	0.75 mm²
Terminations per pole	1
Connection cross section stranded mm <sup>2</sup> min.	0.75 mm²
Connection cross section stranded mm <sup>2</sup> max.	6 mm²
Connection cross section stranded AWG min.	16 AWG
Connection cross section stranded AWG max.	10 AWG
sheath strip length	42 mm
Wire strip length	8 mm



Model	female
Connection type	screw connection
Degree of protection (IP)	IP66/68 (3m;2h) /IP69

#### Material

Housing material	Polyamide
halogen free	yes
Contact material	CuZn
Fire load	0.52 kWh
Insulation components continous temperature	100 °C
Surface finish	Silver-plated

#### Dimensions

Length	97 mm
Width	59 mm
Height	38 mm

### Classification

ECLASS 11	
ECLASS 8.1	27440605
ETIM 7.0	EC002560
ETIM 6.0	EC002560
ETIM 5.0	EC002560
ETIM 4.0	EC002560

#### Note

Note	RST® terminals with screw clamping allow the connection of
	conductors without special preparation (without ferrules) according to
	EN 60999-1.

### Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

## Accessories


Commercial Art.No.:	Article-type description:	Description:
99.413.6205.2	Cover for female connector GL	RST20i3/2 cover piece, for covering unused female connectors, with fastening belt, color light grey
Z5.564.4553.0	Cover for female connector GL	RST20i3/2 cover piece, for covering unused female connectors, color light grey

# Fits with

	Article-type description:	Description:
Art.No.:		



96.020.0153.0	Distributor RST20I2V 3P1 F V GL	RST20i3/2 distribution block, 2 pole, application 250V, 20A, 1 input
		and 3 outputs, with fastening option, coding color light grey, color of housing light grey



		6			А
<u>A - A</u>			unassemb nbestück	Weitergabe sovie Vervielfähigung-dieses Dokuments, Verwertung und Mitteliung senes Inhalts sind verbaten, soweit nicht uusdrücklich gestattet. The reproduction, distribution and utilization of this document as well as the communication of its conents to others without express autorization is prohibited.	A 1 2 3 4 5 6 7 7 8 9 10 11 12 13 14 15 16 17 18
					18 19 20 M1 M2 M3 L G i 11.1 12.1
		und Deklarationsliste nach W-TG			:45:26 1.000
. decta etten Änderungen	rable ho 1.Verwe	th Wieland document UU-TOM-05/03 izardous substances) to be declare ndung:	Blott: 1	VOD	2-16T09
	First U	'eichnung Nr./Drawing No.	Sheet: 1	of 1 Index	2006-02
. Kneitz -	Τ	96.021.425	3.0 01	1K	) Kneitz (
-	I	Maβe in mm∕Dimensions o	are in mm		W1019
icement for: - Benennung/Title					_4 CAD
BUCHSENTEL_MIT_DOPPELZUGENTL female connector with double cord grip Schraubanschluss ohne Drahtschutz/screw-connection without wire protection 6 QU-PEM-08/91					960214253001K_4 CADW1019 Kneitz 2006-02-16T09:45:26 1.000
		6	UU-H	-EM-08/91	