

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM18RK471SN1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-eu/products/productdetail?partno=BLM18RK471SN1%23

BLM18RK471SN1#


"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > BLM18RK471SN1B BLM18RK471SN1D BLM18RK471SN1J



Appearance & Shape





0.8±0.1

(in mm)

The chip ferrite beads BLM series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground. The nickel barrier structure of the external electrodes provides excellent solder heat resistance.

BLM R series can be used in a digital Interface. Resistance of BLM R series especially grows in the lower frequency range. Therefore BLM_R series is less effective for digital signal waveform at low frequency range and can suppress the ringing.



	Other Usage	For general
i		ч

Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of BLM18RK471SN1# from the official website of Murata Manufacturing Co. Ltd.

Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM18RK471SN1%23

BLM18RK471SN1#

"#" indicates a package specification code.

Specifications

Shape	SMD
Size Code (in mm)	1608
Size Code (in inch)	0603
Length	1.6mm
Length Tolerance	±0.15mm
Width	0.8mm
Width Tolerance	±0.15mm
Thickness	0.8mm
Thickness Tolerance	±0.15mm
Impedance (at 100MHz)	470Ω
Impedance (at 100MHz) Tolerance	±25%
Rated Current (at 85°C)	200mA
Rated Current (at 125°C)	200mA
DC Resistance(max.)	0.5Ω
Operating Temperature Range	-55℃ to 125℃
Mass(typ.)	0.005g
Number of Circuit	1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance police. Please check with our sales representatives or product engineers before ordering

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date


Please download the latest datasheet of BLM18RK471SN1# from the official website of Murata Manufacturing Co. Ltd.


Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=BLM18RK471SN1%23

BLM18RK471SN1#

"#" indicates a package specification code.

Product Data





Impedance-Frequency Characteristics

Equivalent Circuit

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3