


## Data sheet

Commercial Art.No.: 25.751.0853.0

Printed circuit board terminal 8285 / 8 TOP V

PCB terminal with front/top screw connection, 8 poles, printed version, with solder pin (3.5mm), max. cross section: 2.5 mm<sup>2</sup>, pitch: 5.08 mm, type of packing: carton, color: grey



Commercial Art.No.	25.751.0853.0
EAN	4015573522732
Order Unit	50

Certificates / Approvals



## Technical data

### General

Modular spacing	5.08 mm
Connection type	screw connection
Soldering process	Wave soldering
Packaging	Carton
Number of poles	8
Conductor to circuit board	90°
Number of levels	1
Integrated test socket	No
Insulation plate	No
Retaining pins	No
Marking	No

### Technical data

Nominal cross section	2.5 mm <sup>2</sup>
Rated current	16 A
Overvoltage Category I	1000 V
Overvoltage Category II	690 V
Overvoltage Category III	250 V
Rated impulse voltage	4 kV
Wire strip length	9 mm

### Connection Data

Minimum cross section solid	0.14 mm <sup>2</sup>
Maximum cross section solid	4 mm <sup>2</sup>
Minimum cross section fine stranded	0.14 mm <sup>2</sup>
Maximum cross section fine stranded	2.5 mm <sup>2</sup>

Wire strip length	9 mm
-------------------	------

**Technical Data UL/CSA**

Cross section UL	22-12 AWG
Voltage UL	300 V
Current field wiring	20 A
Current factory wiring	25 A
Cross section CSA	22-12 AWG
Voltage CSA	300 V
Current CSA	20 A

**Other**

Type of insulation material	Thermoplastic
Color	Grey
Height	20.5 mm
Length	43.14 mm
Depth	18.5 mm
Material attachment screw	Steel
Material contact base	E-Cu
Material contact surface	Sn

**Classification**


ECLASS 11	
ECLASS 8.1	27440401
ETIM 7.0	EC002643
ETIM 6.0	EC002643
ETIM 5.0	EC002643
ETIM 4.0	EC002643

**Product compliance**

ROHS conformity status	Compliant
REACH-SVHC conformity status	Compliant

**Fits with**

Commercial Art.No.:	Article-type description:	Description:
07.300.4753.0	End plate AP 8185 TOP N	



für folgende Tabellen-Zchnng.  
 25.751.0253.0 8285/.. TOP V

LP.KLEMME  
 25.751.0253.0 10W  
 16.10.2007 DÜT  
 M 2:1