


PART NO.


CH23-1220LF


REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	Α	RELEASED	Asha	26/11/11	Veena	26/11/11		10/12/11

**RoHS** 

Compliant







PCB Mounting Layout

Dimensions: Millimetres

## Specifications:

Material:

Housing : PBT + 30% GF black colour
Contact : Phosphor bronze 0.2 mm thick

Tin plated over nickel

Current rating : 2 A ac / dc Voltage rating : 500 V ac / dc

 $\begin{array}{ll} \text{Contact resistance} & : 30 \text{ m}\Omega \\ \text{Insulation resistance} & : 500 \text{ M}\Omega \end{array}$ 

Temperature range : -55°C to +85°C

Humidity : 40°C and 90 - 95% RH for 96 hrs

General Tolerance			
Dimension : 0	±0.3		
0	±0.2		
Angle: ±3° 0	±0.1		

## Part Number Table

Description	Part Number		
Battery Holder, DIP, 12 mm	CH23-1220LF		

DRAWN BY:	DATE:
Asha	26/11/11
CHECKED BY:	DATE:
Veena	26/11/11
APPROVED BY:	DATE:
	10/12/11

DRAWI	NG TITLE:					
Battery Holder						
SIZE A	DWG NO.	M10002766	ELEC CH 2	REV A		
SCALE: NTS		U.O.M.: mm		SHEET: 1 OF	- 1	