



WINSTAR Display Co.,Ltd.
華凌光電股份有限公司



Winstar Display Co., LTD

華凌光電股份有限公司

WEB: <https://www.winstar.com.tw> E-mail: sales@winstar.com.tw



SPECIFICATION

CUSTOMER : _____

MODULE NO.: **FC001502E21XXXXXX00**

| | |
|--|--|
| APPROVED BY: (FOR CUSTOMER USE ONLY) | PCB VERSION: _____ DATA: _____ |
|--|--|

| SALES BY | APPROVED BY | CHECKED BY | PREPARED BY |
|----------|-------------|------------|-------------|
| | | | |

| VERSION | DATE | REVISED PAGE NO. | SUMMARY |
|---------|------|---------------------|---------|
| | | | |

| | | | | | | | |
|----------------|-------------------------|----------------|-------------------------|---------------------|--|-------------------|---|
| 客戶 Customer | 華凌光電 | 料號 PN NO | FC001502E2 1XXXXXX00 | 訂單編號 PO NO | | 出貨日期 Ship Date | |
| 機種 Part no | FC001502E2 1XXXXXX00 | 訂單數量 PO Qty | | 抽樣數 Sampling Qty | | 判定 Finding | <input checked="" type="checkbox"/> 允收 <input type="checkbox"/> 拒收 |

| 檢驗項目 Inspection Items | 規 格 Specification | | 檢 驗 結 果 Inspection Result | | | 備註 |
|--------------------------|----------------------|--------|------------------------------|---|--------|----|
| PIN數 | 32 | | 32 | | | OK |
| PITCH(P) | 0.50 | ± 0.03 | 0.50 | ~ | 0.51 | OK |
| 線徑(A) | 0.30 | ± 0.02 | 0.28 | ~ | 0.30 | OK |
| 裸銅(S) | 4.00 | ± 1.00 | 3.94 | ~ | 4.18 | OK |
| 裸銅(S) | 4.00 | ± 1.00 | 3.73 | ~ | 4.05 | OK |
| 補強板(d) | 6.00 | ± 1.50 | 5.99 | ~ | 6.10 | OK |
| 端子厚(TT) | 0.30 | ± 0.05 | 0.33 | ~ | 0.35 | OK |
| 邊寬(M) | 0.35 | ± 0.15 | 0.25 | ~ | 0.41 | OK |
| 總寬(W) | 16.50 | ± 0.15 | 16.38 | ~ | 16.46 | OK |
| 長度(L) | 150.00 | ± 3.00 | 149.96 | ~ | 150.07 | OK |

| L | 補強板(d) | 總寬(W) | 端子厚(TT) | 裸銅(S) | PITCH(P) | 線徑(A) | 邊寬(M) | 貼雙面膠 |
|---------------|----------|-------------|-------------|-----------|------------|--------|--------|-----------------|
| 15 ~ 99 ± 2 | 特殊 ± 0.5 | A ± 0.1 | 0.3 ± 0.05 | 4 ↓ ± 0.5 | 0.5 ± 0.03 | ± 0.02 | ± 0.15 | 長 + 0.8 / - 0.3 |
| 100 ~ 199 ± 3 | ± 1.5 | 10 ↑ ± 0.15 | 0.2 ± 0.05 | 4 ↑ ± 1 | 1.0 ± 0.05 | | | 寬 ± 0.5 |
| 200 ~ 299 ± 4 | | | 0.15 ± 0.05 | | | | | |
| 300 ~ 499 ± 5 | | | | | | | | |
| 500 ~ 749 ± 8 | | | | | | | | |
| | | | | | | | | |



