

Data sheet

Commercial Art.No.: 80.020.2004.0

Solid state relay WRS-SSDC-60V5A

WRS-solid-state-relays DC, solid state relay not plugable, with LED, open module housing WEB 1002. 80x12,5mm (HxW), control voltage: 24V DC, output: 60 V DC/5A



Commercial Art.No.	80.020.2004.0
EAN	4015573440845
Order Unit	10

Certificates / Approvals



Technical data

General

Modular version	No
-----------------	----

Technical data

Connection type	screw connection
Type of excitation	DC
Min. connection voltage	3 V
Max. connection voltage	60 V
Rated operating current DC	5 A
Min. control voltage	24 V

Dimensions

Depth	59 mm
Width	12.5 mm
Height	80 mm

Classification

ECLASS 11	
ECLASS 8.1	27371014
ETIM 7.0	EC002055
ETIM 6.0	EC002055
ETIM 5.0	EC002055
ETIM 4.0	EC002055

ETIM 3.0	EC002055
----------	----------

Product compliance

ROHS conformity status	Compliant/Exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1