



		尺寸公差(mm)			
		0	>30	>60	>100
Rated current	15A	~	~	~	~
Rated voltage	300V	30	60	100	150
Coil/Contact dielectric voltage	4000V/S	~	~	~	>150
Dielectric voltage between contact	2500V/S	±0.20	±0.30	±0.50	±0.70 ±1.00
Screw torque	1.0Nm				
External connection wire	20-14/0.5-2.5W				
Ambient temperature	G/mm <sup>2</sup>				
Key controlled symbol	-45~+85℃				
Conform to RoHS	*				

Printing for laser marking/printing content is clear ,no broken line/rect  
 Seal literal reference according to the foot position in the drawing

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE: A4	TYPE: PRODUCT DRAWING	SCALE: 1:1	REV	TO-1

NO.	DESCRIPTION	MATERIAL NO.	QTY	MATERIAL	NOTES
1	DSRT05A-F3-00A(H)-N	300190000132	1		

MATERIAL: / SURFACE: /

MAT. NO.: 300200000061

STATUS: /

APPD: /

CHKD: /

DRAFT: /

DRAWING NO.: 30000369

DESCRIPTION: DSRT05A-F3-00A(H)

NINGBO DEGSON ELECTRICAL CO., LTD