

# DC AXIAL FAN

JAMICON®

## 40X40X10 mm

## KF0410-03 KF0410-08 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS											
Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0410B5H	Dual Ball	5	4.25~5.75	6.42	0.129	6000	0.13	0.65	0.8	26.4	16
KF0410B5M				5.75	0.106	5400	0.09	0.45	0.5	24.4	
KF0410B5L				4.37	0.067	4200	0.07	0.35	0.4	19.9	
KF0410S5H	Sleeve			6.42	0.129	6000	0.20	1.00	1.2	26.4	
KF0410S5M				5.75	0.106	5400	0.10	0.50	0.8	24.4	
KF0410S5L				4.37	0.067	4200	0.08	0.40	0.6	19.9	
KF0410B1H	Dual Ball	12	10.2~13.8	6.42	0.129	6000	0.07	0.84	0.8	26.4	
KF0410B1M				5.75	0.106	5400	0.06	0.72	0.7	24.4	
KF0410B1L				4.37	0.067	4200	0.05	0.60	0.6	19.9	
KF0410S1H	Sleeve			6.42	0.129	6000	0.08	0.96	1.2	26.4	
KF0410S1M				5.75	0.106	5400	0.07	0.84	0.8	24.4	
KF0410S1L				4.37	0.067	4200	0.06	0.72	0.7	19.9	
KF0410B2S	Dual Ball	24	20.4~27.6	6.97	0.159	6600	0.06	1.44	1.4	29.3	
KF0410B2H				6.42	0.129	6000	0.05	1.20	1.2	26.4	
KF0410B2M				5.75	0.106	5400	0.04	0.96	1.0	24.4	
KF0410B2L	Sleeve			4.37	0.067	4200	0.03	0.72	0.8	19.9	
KF0410S2H				6.42	0.129	6000	0.05	1.20	1.2	26.4	
KF0410S2M				5.75	0.106	5400	0.04	0.96	1.0	24.4	
KF0410S2L	4.37	0.067	4200	0.03	0.72	0.8	19.9				

Specifications subject to change without notice

